

RG 500m WINCH

A robust 'no-frills' unit, the 500m winch can be operated from a vehicle battery and is ideal for heavy probes in shallow boreholes



SPECIFICATIONS


| | |
|----------|--|
| Capacity | 530m(1738ft) $\frac{3}{16}$ in four-core cable |
| Speed | 0 – 13m/min (0 – 43ft/min) |
| Motor | 180W at 12VDC |
| Size | 582(w) x 482(l) x 414mm(h) |
| Weight | 52kg excluding cable |

SALES INFORMATION

15 010 000 500m winch including tripod, power and data cable

RG 600m WINCH

Of similar basic construction to the 500m winch, the 600m winch is mains/generator powered for higher speeds in time-critical operations.



SPECIFICATIONS


| | |
|----------|--|
| Capacity | 630m(2066ft) $\frac{3}{16}$ in four-core cable |
| Speed | 0 – 15m/min (0 - 49ft/min) |
| Motor | 540W at 110/220VAC |
| Size | 622(w) x 696(l) x 370mm(h) |
| Weight | 80kg excluding cable |

SALES INFORMATION

15 025 000 600m winch including tripod, power and data cable

RG 1000 / 2000m WINCH

The standard unit for truck-mounted operations in deep boreholes, the 2000m winch includes an integral depth wheel and an automatic level wind.



SPECIFICATIONS

| | |
|----------|--|
| Capacity | 2030m (6658ft) $\frac{3}{16}$ in four-core cable |
| | 1030m (3378ft) $\frac{1}{4}$ in coaxial cable |
| Speed | 0 – 30m/min (0 - 99ft/min) |
| Motor | 2hp (1.5kW) at 110/220VAC |
| Size | 605(w) x 1060(l) x 735mm(h) |
| Weight | 142kg excluding cable |

SALES INFORMATION

15 015 000 winch for $\frac{3}{16}$ in four-core cable includes tripod, power and data cable

15 020 000 winch for $\frac{1}{4}$ in coaxial cable includes tripod, power and data cable

RG 3000m WINCH

Single-drum electric draw-works for deeper hole and oil/gas investigations.

SPECIFICATIONS

| | |
|------------|---|
| Capacity | 3,000m (9840ft) $\frac{3}{16}$ " cable |
| Speed | core: 0.2 - 34m/min rim: 0.5 - 100m/min |
| Pull | core: 765 - 1,350kg rim: 255 - 460kg |
| Motor | 440VAC 3-Phase 4kVA |
| Dimensions | 1000(w) x 1100(l) x 900mm(h) |
| Weight | 415kg excluding cable 706kg with 3000m cable |

SALES INFORMATION

15 040 001 winch for $\frac{3}{16}$ in four-core cable includes tripod, power and data cable

15 040 002 automatic level winding system

15 057 000 remote control kit

15 050 000 set of two sheave wheels

15 055 000 weight/tension device (in-line)

