

## ○ Mini Winch, SMART Winch & 500m Winch

RG produces a range of winch designs suitable for most slim-hole logging requirements. Each winch is precision engineered for reliable operation under harsh field conditions. RG winches support standard sizes of logging and video cables and are compatible with the Micrologger2 surface system and standard RG slim-hole probes at depths up to 2,000m.

### Mini winch

The RG Mini winch is portable, compact and robust. Its basic 'no-frills' design is aimed at long-term reliability under arduous conditions.

### SMART winch

The SMART winch is battery operated and can be controlled remotely from the logging PC. Features include an integral measure wheel and depth display, automatic level wind and an electric brake.

### 500m winch

A robust 'no-frills' unit, the 500m winch can be operated from a vehicle battery and is ideal for heavier probes in shallow boreholes.

### Mini winch

#### > Specification

Capacity	175m (575') 3/16" 4-core cable
Speed	0 – 17.5m/min (0 – 57ft/min) on full drum (12VDC operation)
Motor	550W (12 – 24VDC)
Size	340(w) x 400(l) x 320mm(h)
Weight	19kg excluding cable

#### > Sales Information

I013754	Mini Winch includes power and data cables
I001117	Mini Winch Tripod with Encoder

### SMART winch

#### > Specification

Capacity	180m (590') 3/16" 4-core cable
Speed	0.5 – 15m/min (1.6 – 49ft/min)
Motor	120W at 12VDC
Size	265(w) x 465(l) x 380mm(h)
Weight	24kg excluding cable

#### > Sales Information

I001018	SMART winch for 4.76mm (3/16") four-core cable
---------	--

### 500m winch

#### > Specification

Capacity	530m (1738') 3/16" 4-core cable
Speed	0 – 13m/min (0 – 43ft/min)
Motor	180W at 12VDC
Size	582(w) x 482(l) x 414mm(h)
Weight	52kg excluding cable

#### > Sales Information

I001019	500m winch including tripod, power and data cable
---------	---

RG

